



# Duram S900

## Duram Pty Ltd

Chemwatch Hazard Alert Code: 2

Chemwatch: 5236-16

Version No: 6.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 10/03/2023

Print Date: 24/04/2023

L.GHS.AUS.EN.E

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

|                               |                                     |
|-------------------------------|-------------------------------------|
| Product name                  | Duram S900                          |
| Chemical Name                 | Not Applicable                      |
| Synonyms                      | Duram S900 Clear Penetrative Sealer |
| Proper shipping name          | TURPENTINE SUBSTITUTE               |
| Chemical formula              | Not Applicable                      |
| Other means of identification | Not Available                       |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before initiating use, consider control of exposure by mechanical ventilation. |
|--------------------------|---|

#### Details of the manufacturer or supplier of the safety data sheet

|                         |  |
|-------------------------|--|
| Registered company name | Duram Pty Ltd  |
| Address                 | 51 Prince William Drive Seven Hills NSW 2147 Australia |
| Telephone               | +61 2 9624 4007  |
| Fax                     | +61 2 9624 4079  |
| Website                 | <a href="http://www.duram.com.au">www.duram.com.au</a> |
| Email                   | mail@duram.com.au                                      |

#### Emergency telephone number

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Association / Organisation        | CHEMTREC Australia (Sydney)      |
| Emergency telephone numbers       | +612 9037 2994 24 hours / 7 days |
| Other emergency telephone numbers | Not Available                    |

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

#### Chemwatch Hazard Ratings

|              | Min | Max |              |
|--------------|-----|-----|--------------|
| Flammability | 2   |     |              |
| Toxicity     | 1   |     | 0 = Minimum  |
| Body Contact | 2   |     | 1 = Low      |
| Reactivity   | 1   |     | 2 = Moderate |
| Chronic      | 0   |     | 3 = High     |
|              |     |     | 4 = Extreme  |

|                    |   |
|--------------------|---|
| Poisons Schedule   | S5  |
| Classification [1] | Flammable Liquids Category 3, Aspiration Hazard Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 3 |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI   |

#### Label elements

Duram S900

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

|             |               |
|-------------|---------------|
| Signal word | <b>Danger</b> |
|-------------|---------------|

**Hazard statement(s)**

|        |  |
|--------|--|
| AUH066 | Repeated exposure may cause skin dryness and cracking. |
| H226   | Flammable liquid and vapour.                           |
| H304   | May be fatal if swallowed and enters airways.          |
| H319   | Causes serious eye irritation.                         |
| H336   | May cause drowsiness or dizziness.                     |
| H412   | Harmful to aquatic life with long lasting effects.     |

**Precautionary statement(s) Prevention**

|      |  |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P240 | Ground and bond container and receiving equipment.   |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.              |
| P242 | Use non-sparking tools.  |
| P243 | Take action to prevent static discharges.  |
| P261 | Avoid breathing mist/vapours/spray.  |
| P273 | Avoid release to the environment.  |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection.               |
| P264 | Wash all exposed external body areas thoroughly after handling.                                |

**Precautionary statement(s) Response**

|                |  |
|----------------|--|
| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.   |
| P331           | Do NOT induce vomiting.  |
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                         |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

**Precautionary statement(s) Storage**

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405      | Store locked up.                             |

**Precautionary statement(s) Disposal**

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

**SECTION 3 Composition / information on ingredients**

**Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No        | %[weight] | Name                                       |
|---------------|-----------|--|
| 8052-41-3.    | >60       | <u>Stoddard Solvent</u>                    |
| 95-63-6       | 1-10      | <u>1,2,4-trimethyl benzene</u>             |
| 1330-20-7     | 1-10      | <u>xylene</u>                              |
| Not Available | balance   | Ingredients determined not to be hazardous |

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

**SECTION 4 First aid measures**

**Description of first aid measures**

|             |   |
|-------------|---|
| Eye Contact | If this product comes in contact with the eyes:<br>▶ Wash out immediately with fresh running water. |
|-------------|---|

Continued...

|                     |  |
|---------------------|--|
|                     | <ul style="list-style-type: none"> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>   |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>  |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul> |

#### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short term repeated exposures to xylene:

- ▶ Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- ▶ Pulmonary absorption is rapid with about 60-65% retained at rest.
- ▶ Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> < 50 mm Hg or pCO<sub>2</sub> > 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

#### BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

| Determinant                    | Index                            | Sampling Time                       | Comments |
|--------------------------------|----------------------------------|-------------------------------------|----------|
| Methylhippu-ric acids in urine | 1.5 gm/gm creatinine<br>2 mg/min | End of shift<br>Last 4 hrs of shift |          |

## SECTION 5 Firefighting measures

#### Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

#### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

#### Advice for firefighters

|                              |   |
|------------------------------|---|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are flammable.</li> <li>▶ Moderate fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Moderate explosion hazard when exposed to heat or flame.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include:<br/>carbon dioxide (CO<sub>2</sub>)<br/>other pyrolysis products typical of burning organic material.</p>  |

**Contains low boiling substance:** Closed containers may rupture due to pressure buildup under fire conditions.

HAZCHEM 3Y

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

| <b>Minor Spills</b>                                 | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>   |              |            |                 |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
|---|---|--------------|------------|-----------------|------------|-------------|---------------------------|--|--|--|--|-------------------|---|-------|-----------|---------|------------------------------------|---|--------|--------|--------|------------------------------|---|-------|-----------|------------|----------------------------|---|--------|--------|----------|---|---|--------|--------|------|---------------------|---|-------|-----------|---------------|----------------------------|--|--|--|--|-----------------------------------|---|--------|------------|----------|---|---|--------|------------|------|----------------------------|---|--------|------------|---------|-----------------------------|---|--------|------------|------------|-------------------|---|-------|------------|---------|--------------------------------|---|--------|------------|-----------------|
| <b>Major Spills</b>                                 | <p>Chemical Class: aromatic hydrocarbons<br/>For release onto land: recommended sorbents listed in order of priority.</p> <table border="1"> <thead> <tr> <th>SORBENT TYPE</th> <th>RANK</th> <th>APPLICATION</th> <th>COLLECTION</th> <th>LIMITATIONS</th> </tr> </thead> <tbody> <tr> <td colspan="5"><b>LAND SPILL - SMALL</b></td> </tr> <tr> <td>Feathers - pillow</td> <td>1</td> <td>throw</td> <td>pitchfork</td> <td>DGC, RT</td> </tr> <tr> <td>cross-linked polymer - particulate</td> <td>2</td> <td>shovel</td> <td>shovel</td> <td>R,W,SS</td> </tr> <tr> <td>cross-linked polymer- pillow</td> <td>2</td> <td>throw</td> <td>pitchfork</td> <td>R, DGC, RT</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>3</td> <td>shovel</td> <td>shovel</td> <td>R, I, P,</td> </tr> <tr> <td>treated clay/ treated natural organic - particulate</td> <td>3</td> <td>shovel</td> <td>shovel</td> <td>R, I</td> </tr> <tr> <td>wood fibre - pillow</td> <td>4</td> <td>throw</td> <td>pitchfork</td> <td>R, P, DGC, RT</td> </tr> <tr> <td colspan="5"><b>LAND SPILL - MEDIUM</b></td> </tr> <tr> <td>cross-linked polymer -particulate</td> <td>1</td> <td>blower</td> <td>skidloader</td> <td>R, W, SS</td> </tr> <tr> <td>treated clay/ treated natural organic - particulate</td> <td>2</td> <td>blower</td> <td>skidloader</td> <td>R, I</td> </tr> <tr> <td>sorbent clay - particulate</td> <td>3</td> <td>blower</td> <td>skidloader</td> <td>R, I, P</td> </tr> <tr> <td>polypropylene - particulate</td> <td>3</td> <td>blower</td> <td>skidloader</td> <td>W, SS, DGC</td> </tr> <tr> <td>feathers - pillow</td> <td>3</td> <td>throw</td> <td>skidloader</td> <td>DGC, RT</td> </tr> <tr> <td>expanded mineral - particulate</td> <td>4</td> <td>blower</td> <td>skidloader</td> <td>R, I, W, P, DGC</td> </tr> </tbody> </table> <p><b>Legend</b><br/> DGC: Not effective where ground cover is dense<br/> R: Not reusable<br/> I: Not incinerable<br/> P: Effectiveness reduced when rainy<br/> RT:Not effective where terrain is rugged<br/> SS: Not for use within environmentally sensitive sites<br/> W: Effectiveness reduced when windy<br/> Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;<br/> R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Use only spark-free shovels and explosion proof equipment.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> | SORBENT TYPE | RANK       | APPLICATION     | COLLECTION | LIMITATIONS | <b>LAND SPILL - SMALL</b> |  |  |  |  | Feathers - pillow | 1 | throw | pitchfork | DGC, RT | cross-linked polymer - particulate | 2 | shovel | shovel | R,W,SS | cross-linked polymer- pillow | 2 | throw | pitchfork | R, DGC, RT | sorbent clay - particulate | 3 | shovel | shovel | R, I, P, | treated clay/ treated natural organic - particulate | 3 | shovel | shovel | R, I | wood fibre - pillow | 4 | throw | pitchfork | R, P, DGC, RT | <b>LAND SPILL - MEDIUM</b> |  |  |  |  | cross-linked polymer -particulate | 1 | blower | skidloader | R, W, SS | treated clay/ treated natural organic - particulate | 2 | blower | skidloader | R, I | sorbent clay - particulate | 3 | blower | skidloader | R, I, P | polypropylene - particulate | 3 | blower | skidloader | W, SS, DGC | feathers - pillow | 3 | throw | skidloader | DGC, RT | expanded mineral - particulate | 4 | blower | skidloader | R, I, W, P, DGC |
| SORBENT TYPE  | RANK  | APPLICATION  | COLLECTION | LIMITATIONS     |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| <b>LAND SPILL - SMALL</b>                           |   |              |            |                 |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| Feathers - pillow                                   | 1   | throw        | pitchfork  | DGC, RT         |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| cross-linked polymer - particulate                  | 2   | shovel       | shovel     | R,W,SS          |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| cross-linked polymer- pillow                        | 2   | throw        | pitchfork  | R, DGC, RT      |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| sorbent clay - particulate                          | 3   | shovel       | shovel     | R, I, P,        |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| treated clay/ treated natural organic - particulate | 3   | shovel       | shovel     | R, I            |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| wood fibre - pillow                                 | 4   | throw        | pitchfork  | R, P, DGC, RT   |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| <b>LAND SPILL - MEDIUM</b>                          |   |              |            |                 |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| cross-linked polymer -particulate                   | 1   | blower       | skidloader | R, W, SS        |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| treated clay/ treated natural organic - particulate | 2   | blower       | skidloader | R, I            |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| sorbent clay - particulate                          | 3   | blower       | skidloader | R, I, P         |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| polypropylene - particulate                         | 3   | blower       | skidloader | W, SS, DGC      |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| feathers - pillow                                   | 3   | throw        | skidloader | DGC, RT         |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |
| expanded mineral - particulate                      | 4   | blower       | skidloader | R, I, W, P, DGC |            |             |                           |  |  |  |  |                   |   |       |           |         |                                    |   |        |        |        |                              |   |       |           |            |                            |   |        |        |          |   |   |        |        |      |                     |   |       |           |               |                            |  |  |  |  |                                   |   |        |            |          |   |   |        |            |      |                            |   |        |            |         |                             |   |        |            |            |                   |   |       |            |         |                                |   |        |            |                 |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                      |   |
|----------------------|---|
| <b>Safe handling</b> | <p>The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> |
|----------------------|---|

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

**Contains low boiling substance:**

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
- Vent periodically
- Always release caps or seals slowly to ensure slow dissipation of vapours
- **DO NOT allow clothing wet with material to stay in contact with skin**
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Do NOT use compressed air for filling discharging or handling operations.
- Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes.
- Wait 30 minutes after tank filling ( for large storage tanks)
- before opening hatches or manholes. Even with proper
- grounding and bonding, this material can still accumulate an
- electrostatic charge. If sufficient charge is allowed to
- accumulate, electrostatic discharge and ignition of flammable
- air-vapour mixtures can occur. Be aware of handling
- operations that may give rise to additional hazards that result
- from the accumulation of static charges. These include but are
- not limited to pumping (especially turbulent flow), mixing,
- filtering, splash filling, cleaning and filling of tanks and
- containers, sampling, switch loading, gauging, vacuum truck
- operations, and mechanical movements. These activities may
- lead to static discharge e.g. spark formation. Restrict line
- velocity during pumping in order to avoid generation of
- electrostatic discharge ( $= 1$  m/s until fill pipe submerged to
- twice its diameter, then  $= 7$  m/s). Avoid splash filling.
- Do NOT use compressed air for filling, discharging, or handling operations
  - Avoid all personal contact, including inhalation.
  - Wear protective clothing when risk of overexposure occurs.
  - Use in a well-ventilated area.
  - Prevent concentration in hollows and sumps.
  - **DO NOT enter confined spaces until atmosphere has been checked.**
  - Avoid smoking, naked lights or ignition sources.
  - Avoid generation of static electricity.
  - **DO NOT use plastic buckets.**
  - Earth all lines and equipment.
  - Use spark-free tools when handling.
  - Avoid contact with incompatible materials.
  - **When handling, DO NOT eat, drink or smoke.**
  - Keep containers securely sealed when not in use.
  - Avoid physical damage to containers.
  - Always wash hands with soap and water after handling.
  - Work clothes should be laundered separately.
  - Use good occupational work practice.
  - Observe manufacturer's storage and handling recommendations contained within this SDS.
  - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

**Other information**

- Store in original containers in approved flammable liquid storage area.
  - Store away from incompatible materials in a cool, dry, well-ventilated area.
  - **DO NOT store in pits, depressions, basements or areas where vapours may be trapped.**
  - No smoking, naked lights, heat or ignition sources.
  - Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access.
  - Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances.
  - Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems.
  - Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors.
  - Keep adsorbents for leaks and spills readily available.
  - Protect containers against physical damage and check regularly for leaks.
  - Observe manufacturer's storage and handling recommendations contained within this SDS.
- In addition, for tank storages (where appropriate):
- Store in grounded, properly designed and approved vessels and away from incompatible materials.
  - For bulk storages, consider use of floating roof or nitrogen blanketed vessels; where venting to atmosphere is possible, equip storage tank vents with flame arrestors; inspect tank vents during winter conditions for vapour/ ice build-up.
  - Storage tanks should be above ground and diked to hold entire contents.

**Conditions for safe storage, including any incompatibilities**

**Suitable container**

- Pails.
- Packing as supplied by manufacturer.
  - Plastic containers may only be used if approved for flammable liquid.
  - Check that containers are clearly labelled and free from leaks.
  - For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
  - For materials with a viscosity of at least 2680 cSt. (23 deg. C)
  - For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
  - Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.
  - Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with

|                                |  |
|--------------------------------|--|
|                                | <p>inner and outer packages</p> <p>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</p> |
| <b>Storage incompatibility</b> | <p>▶ Avoid reaction with oxidising agents</p> <p>▶ Avoid strong acids, bases.</p>  |

## SECTION 8 Exposure controls / personal protection

### Control parameters

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

| Source                       | Ingredient       | Material name               | TWA                            | STEL                            | Peak          | Notes         |
|------------------------------|------------------|-----------------------------|--------------------------------|---------------------------------|---------------|---------------|
| Australia Exposure Standards | Stoddard Solvent | White spirits               | 790 mg/m <sup>3</sup>          | Not Available                   | Not Available | Not Available |
| Australia Exposure Standards | xylene           | Xylene (o-, m-, p- isomers) | 80 ppm / 350 mg/m <sup>3</sup> | 655 mg/m <sup>3</sup> / 150 ppm | Not Available | Not Available |

#### Emergency Limits

| Ingredient              | TEEL-1                | TEEL-2                  | TEEL-3                    |
|-------------------------|-----------------------|-------------------------|---------------------------|
| Stoddard Solvent        | 300 mg/m <sup>3</sup> | 1,800 mg/m <sup>3</sup> | 29500** mg/m <sup>3</sup> |
| 1,2,4-trimethyl benzene | 140 mg/m <sup>3</sup> | 360 mg/m <sup>3</sup>   | 2,200 mg/m <sup>3</sup>   |
| 1,2,4-trimethyl benzene | Not Available         | Not Available           | 480 ppm                   |
| xylene                  | Not Available         | Not Available           | Not Available             |

| Ingredient              | Original IDLH            | Revised IDLH  |
|-------------------------|--------------------------|---------------|
| Stoddard Solvent        | 20,000 mg/m <sup>3</sup> | Not Available |
| 1,2,4-trimethyl benzene | Not Available            | Not Available |
| xylene                  | 900 ppm                  | Not Available |

#### Occupational Exposure Banding

| Ingredient              | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|-------------------------|-----------------------------------|----------------------------------|
| 1,2,4-trimethyl benzene | E                                 | ≤ 0.1 ppm                        |

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

#### MATERIAL DATA

NOTE P: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 0.01% w/w benzene (EINECS No 200-753-7). Note E shall also apply when the substance is classified as a carcinogen. This note applies only to certain complex oil-derived substances in Annex VI. European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

### Exposure controls

| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> |                                 |   |  |  |   |                                  |  |   |                                  |
|---|---|---------------------------------|---|--|--|---|----------------------------------|--|---|----------------------------------|
|   | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s<br/>(50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s<br/>(100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s<br/>(200-500 f/min.)</td> </tr> </tbody> </table>  | Type of Contaminant:            | Air Speed:  | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s<br>(50-100 f/min.)                            | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s<br>(100-200 f/min.)    | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s<br>(200-500 f/min.)             |                                  |
|   | Type of Contaminant:  | Air Speed:                      |   |  |  |   |                                  |  |   |                                  |
|   | solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s<br>(50-100 f/min.) |   |  |  |   |                                  |  |   |                                  |
|   | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)   | 0.5-1 m/s<br>(100-200 f/min.)   |   |  |  |   |                                  |  |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s<br>(200-500 f/min.)   |                                 |   |  |  |   |                                  |  |   |                                  |
| <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> | Lower end of the range  | Upper end of the range          | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents  | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity  | 3: Intermittent, low production. | 3: High production, heavy use  | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Lower end of the range  | Upper end of the range  |                                 |   |  |  |   |                                  |  |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                                 |   |  |  |   |                                  |  |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                                 |   |  |  |   |                                  |  |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                                 |   |  |  |   |                                  |  |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                                 |   |  |  |   |                                  |  |   |                                  |
| <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of</p>   |   |                                 |   |  |  |   |                                  |  |   |                                  |
|   |   |                                 |   |  |  |   |                                  |  |   |                                  |

|  |   |
|--|---|
|  | <p>1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> <ul style="list-style-type: none"> <li>- Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.</li> <li>- Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.</li> <li>- Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)</li> </ul>   |
| <b>Individual protection measures, such as personal protective equipment</b> |    |
| <b>Eye and face protection</b>   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |
| <b>Skin protection</b>   | See Hand protection below   |
| <b>Hands/feet protection</b>   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>- frequency and duration of contact,</li> <li>- chemical resistance of glove material,</li> <li>- glove thickness and</li> <li>- dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>- Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>- Excellent when breakthrough time &gt; 480 min</li> <li>- Good when breakthrough time &gt; 20 min</li> <li>- Fair when breakthrough time &lt; 20 min</li> <li>- Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>   | See Other protection below  |
| <b>Other protection</b>  | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul>   |

**Recommended material(s)****GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Duram S900

| Material          | CPI |
|-------------------|-----|
| PE/EVAL/PE        | A   |
| TEFLON            | A   |
| BUTYL             | C   |
| BUTYL/NEOPRENE    | C   |
| HYPALON           | C   |
| NAT+NEOPR+NITRILE | C   |
| NATURAL RUBBER    | C   |
| NATURAL+NEOPRENE  | C   |
| NEOPRENE          | C   |
| NEOPRENE/NATURAL  | C   |
| NITRILE           | C   |
| NITRILE+PVC       | C   |
| PVA               | C   |
| PVC               | C   |
| PVDC/PE/PVDC      | C   |
| SARANEX-23        | C   |
| SARANEX-23 2-PLY  | C   |
| VITON             | C   |
| VITON/NEOPRENE    | C   |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Respiratory protection**

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | AX-AUS               | -                    | AX-PAPR-AUS / Class 1  |
| up to 50 x ES                      | -                    | AX-AUS / Class 1     | -                      |
| up to 100 x ES                     | -                    | AX-2                 | AX-PAPR-2 ^            |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

**SECTION 9 Physical and chemical properties****Information on basic physical and chemical properties**

|   |  |  |                |
|---|--|--|----------------|
| <b>Appearance</b>                                   | Clear flammable liquid with a characteristic odour; does not mix with water. |  |                |
| <b>Physical state</b>                               | Liquid   | <b>Relative density (Water = 1)</b>            | 0.9            |
| <b>Odour</b>  | Not Available  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available  | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Applicable   | <b>Decomposition temperature (°C)</b>          | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available  | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | 145  | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | 35   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available  | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Flammable.   | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available  | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available  | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available  | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water</b>                          | Immiscible   | <b>pH as a solution (1%)</b>                   | Not Applicable |
| <b>Vapour density (Air = 1)</b>                     | Not Available  | <b>VOC g/L</b>                                 | Not Available  |

**SECTION 10 Stability and reactivity**

|                   |               |
|-------------------|---------------|
| <b>Reactivity</b> | See section 7 |
|-------------------|---------------|

|   |  |
|---|--|
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

### Information on toxicological effects

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse. A slow heart rate and low blood pressure may also occur.</p> <p>Alkylbenzenes are not generally toxic except at high levels of exposure. Their breakdown products have low toxicity and are easily eliminated from the body.</p> <p>High inhaled concentrations of mixed hydrocarbons may produce narcosis characterised by nausea, vomiting and lightheadedness. Inhalation of aerosols may produce severe pulmonary oedema, pneumonitis and pulmonary haemorrhage. Inhalation of petroleum hydrocarbons consisting substantially of low molecular weight species (typically C2-C12) may produce irritation of mucous membranes, incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and anaesthetic stupor. Massive exposures may produce central nervous system depression with sudden collapse and deep coma; fatalities have been recorded. Irritation of the brain and/or apnoeic anoxia may produce convulsions. Although recovery following overexposure is generally complete, cerebral micro-haemorrhage of focal post-inflammatory scarring may produce epileptiform seizures some months after the exposure. Pulmonary episodes may include chemical pneumonitis with oedema and haemorrhage. The lighter hydrocarbons may produce kidney and neurotoxic effects. Pulmonary irritancy increases with carbon chain length for paraffins and olefins. Alkenes produce pulmonary oedema at high concentrations. Liquid paraffins may produce anaesthesia and depressant actions leading to weakness, dizziness, slow and shallow respiration, unconsciousness, convulsions and death. C5-7 paraffins may also produce polyneuropathy. Aromatic hydrocarbons accumulate in lipid rich tissues (typically the brain, spinal cord and peripheral nerves) and may produce functional impairment manifested by nonspecific symptoms such as nausea, weakness, fatigue and vertigo; severe exposures may produce inebriation or unconsciousness. Many of the petroleum hydrocarbons are cardiac sensitisers and may cause ventricular fibrillations. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination</p> <p>Exposure to white spirit, in a controlled inhalation study using volunteers either at rest or during exercise, (1000 or 2500 mg/m<sup>3</sup> for 30 minutes) produced a linear relationship between alveolar and arterial concentrations of the individual solvent components. Pulmonary absorption of the aliphatics ranged from 46-59%, whilst that of aromatic ranged from 58-70%. Although systemic absorption was greater during exercise, the proportion of circulating aliphatic to aromatic components decreased with increased activity. Exposure to 2500 - 5000 mg/m<sup>3</sup> produces nausea and vertigo.</p> <p>Xylene is a central nervous system depressant. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> |
| <b>Ingestion</b>    | <p>Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging, pulmonary oedema, progressing to chemical pneumonitis; serious consequences may result.</p> <p>Signs and symptoms of chemical (aspiration) pneumonitis may include coughing, gasping, choking, burning of the mouth, difficult breathing, and bluish coloured skin (cyanosis).</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Ingestion of petroleum hydrocarbons may produce irritation of the pharynx, oesophagus, stomach and small intestine with oedema and mucosal ulceration resulting; symptoms include a burning sensation in the mouth and throat. Large amounts may produce narcosis with nausea and vomiting, weakness or dizziness, slow and shallow respiration, swelling of the abdomen, unconsciousness and convulsions. Myocardial injury may produce arrhythmias, ventricular fibrillation and electrocardiographic changes. Central nervous system depression may also occur. Light aromatic hydrocarbons produce a warm, sharp, tingling sensation on contact with taste buds and may anaesthetise the tongue. Aspiration into the lungs may produce coughing, gagging and a chemical pneumonitis with pulmonary oedema and haemorrhage.</p>  |
| <b>Skin Contact</b> | <p>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.</p>  |

|  |   |  |
|--|---|--|
|  | <p>Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Aromatic hydrocarbons may produce skin irritation, vasodilation with erythema and changes in endothelial cell permeability. Systemic intoxication, resulting from contact with the light aromatics, is unlikely due to the slow rate of permeation. Branching of the side chain appears to increase percutaneous absorption.</p>  |  |
| <p style="text-align: center;"><b>Eye</b></p>              | <p>Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</p> <p>Petroleum hydrocarbons may produce pain after direct contact with the eyes. Slight, but transient disturbances of the corneal epithelium may also result. The aromatic fraction may produce irritation and lachrymation.</p> <p>The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.</p>   |  |
| <p style="text-align: center;"><b>Chronic</b></p>          | <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p> <p>On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects.</p> <p>Repeated or prolonged exposure to mixed hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory loss, tremor in the fingers and tongue, vertigo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and anaemia and degenerative changes in the liver and kidney. Chronic exposure by petroleum workers, to the lighter hydrocarbons, has been associated with visual disturbances, damage to the central nervous system, peripheral neuropathies (including numbness and paraesthesias), psychological and neurophysiological deficits, bone marrow toxicities (including hypoplasia possibly due to benzene) and hepatic and renal involvement. Chronic dermal exposure to petroleum hydrocarbons may result in defatting which produces localised dermatoses.</p> <p>Surface cracking and erosion may also increase susceptibility to infection by microorganisms. One epidemiological study of petroleum refinery workers has reported elevations in standard mortality ratios for skin cancer along with a dose-response relationship indicating an association between routine workplace exposure to petroleum or one of its constituents and skin cancer, particularly melanoma. Other studies have been unable to confirm this finding.</p> <p>Hydrocarbon solvents are liquid hydrocarbon fractions derived from petroleum processing streams, containing only carbon and hydrogen atoms, with carbon numbers ranging from approximately C5-C20 and boiling between approximately 35-370 deg C. Many of the hydrocarbon solvents have complex and variable compositions with constituents of 4 types, alkanes (normal paraffins, isoparaffins, and cycloparaffins) and aromatics (primarily alkylated one- and two-ring species). Despite the compositional complexity, most hydrocarbon solvent constituents have similar toxicological properties, and the overall toxicological hazards can be characterized in generic terms. Hydrocarbon solvents can cause chemical pneumonitis if aspirated into the lung, and those that are volatile can cause acute CNS effects and/or ocular and respiratory irritation at exposure levels exceeding occupational recommendations. Otherwise, there are few toxicologically important effects. The exceptions, n-hexane and naphthalene, have unique toxicological properties</p> <p>Animal studies:<br/>No deaths or treatment related signs of toxicity were observed in rats exposed to light alkylate naphtha (paraffinic hydrocarbons) at concentrations of 668, 2220 and 6646 ppm for 6 hrs/day, 5 days/wk for 13 weeks. Increased liver weights and kidney toxicity (male rats) was observed in high dose animals. Exposure to pregnant rats at concentrations of 137, 3425 and 6850 ppm did not adversely affect reproduction or cause maternal or foetal toxicity. Lifetime skin painting studies in mice with similar naphthas have shown weak or no carcinogenic activity following prolonged and repeated exposure. Similar naphthas/distillates, when tested at nonirritating dose levels, did not show any significant carcinogenic activity indicating that this tumorigenic response is likely related to chronic irritation and not to dose. The mutagenic potential of naphthas has been reported to be largely negative in a variety of mutagenicity tests. The exact relationship between these results and human health is not known. Some components of this product have been shown to produce a species specific, sex hormonal dependent kidney lesion in male rats from repeated oral or inhalation exposure. Subsequent research has shown that the kidney damage develops via the formation of an alpha-2u-globulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, the kidney effects resulting from this mechanism are not relevant in human.</p> <p>Follicular dermatitis may develop rapidly on repeated immersion of the hands and forearms in white spirits. A Belgian report, produced in 1958, described sub-chronic toxicity amongst workers exposed to white spirit (83% paraffins, 17% aromatics) over a 4 month period. These workers complained of nausea and vomiting and one developed aplastic anaemia; bone marrow depression was confirmed. This employee died several months later as a result of septicaemia. Bone marrow depression, associated with human exposure, might be explained by the presence of myelotoxic compounds, the most notable being benzene.</p> <p>Prolonged or repeated contact with xylenes may cause defatting dermatitis with drying and cracking. Chronic inhalation of xylenes has been associated with central nervous system effects, loss of appetite, nausea, ringing in the ears, irritability, thirst anaemia, mucosal bleeding, enlarged liver and hyperplasia. Exposure may produce kidney and liver damage. In chronic occupational exposure, xylene (usually mixed with other solvents) has produced irreversible damage to the central nervous system and ototoxicity (damages hearing and increases sensitivity to noise), probably due to neurotoxic mechanisms.</p> <p>Industrial workers exposed to xylene with a maximum level of ethyl benzene of 0.06 mg/l (14 ppm) reported headaches and irritability and tired quickly. Functional nervous system disturbances were found in some workers employed for over 7 years whilst other workers had enlarged livers. Xylene has been classed as a developmental toxin in some jurisdictions.</p> <p>Small excess risks of spontaneous abortion and congenital malformation were reported amongst women exposed to xylene in the first trimester of pregnancy. In all cases, however, the women were also been exposed to other substances. Evaluation of workers chronically exposed to xylene has demonstrated lack of genotoxicity. Exposure to xylene has been associated with increased risks of haemopoietic malignancies but, again, simultaneous exposure to other substances (including benzene) complicates the picture. A long-term gavage study to mixed xylenes (containing 17% ethyl benzene) found no evidence of carcinogenic activity in rats and mice of either sex.</p> <p>Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result. Some individuals show severe eye damage following prolonged exposure to 800 ppm of the vapour.</p> <p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).<br/>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]</p> |  |
| <p style="text-align: center;"><b>Duram S900</b></p>       | <p style="text-align: center;"><b>TOXICITY</b></p> <p>Not Available</p>   | <p style="text-align: center;"><b>IRRITATION</b></p> <p>Not Available</p>                |
| <p style="text-align: center;"><b>Stoddard Solvent</b></p> | <p style="text-align: center;"><b>TOXICITY</b></p> <p>Dermal (rabbit) LD50: &gt;3000 mg/kg<sup>[1]</sup></p>  | <p style="text-align: center;"><b>IRRITATION</b></p> <p>Eye (hmn) 470 ppm/15m irrit.</p> |

|                         |   |  |
|-------------------------|---|--|
|                         | Inhalation(Rat) LC50: >5.5 mg/l4h <sup>[1]</sup>  | Eye (rabbit) 500 mg/24h moderate                                 |
|                         | Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|                         |   | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|                         |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| 1,2,4-trimethyl benzene | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                         | Dermal (rabbit) LD50: >3160 mg/kg <sup>[2]</sup>  | Not Available  |
|                         | Inhalation(Rat) LC50: 18 mg/L4h <sup>[2]</sup>  |  |
|                         | Oral (Rat) LD50: 6000 mg/kg <sup>[1]</sup>  |  |
| xylene                  | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                         | Dermal (rabbit) LD50: >1700 mg/kg <sup>[2]</sup>  | Eye (human): 200 ppm irritant                                    |
|                         | Inhalation(Rat) LC50: 5000 ppm4h <sup>[2]</sup>   | Eye (rabbit): 5 mg/24h SEVERE                                    |
|                         | Oral (Mouse) LD50: 2119 mg/kg <sup>[2]</sup>  | Eye (rabbit): 87 mg mild   |
|                         |   | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|                         |   | Skin (rabbit):500 mg/24h moderate                                |
|                         |   | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
| <b>Legend:</b>          | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |  |

|                         |   |
|-------------------------|---|
| STODDARD SOLVENT        | <p>For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss. This product contains ethyl benzene and naphthalene, from which animal testing shows evidence of tumour formation. Cancer-causing potential: Animal testing shows inhaling petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans.</p> <p>Mutation-causing potential: Most studies involving gasoline have returned negative results regarding the potential to cause mutations, including all recent studies in living human subjects (such as in petrol service station attendants).</p> <p>Reproductive toxicity: Animal studies show that high concentrations of toluene (&gt;0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus.</p> <p>Human effects: Prolonged or repeated contact may cause defatting of the skin which can lead to skin inflammation and may make the skin more susceptible to irritation and penetration by other materials.</p> <p>Animal testing shows that exposure to gasoline over a lifetime can cause kidney cancer, but the relevance in humans is questionable.</p>   |
| 1,2,4-TRIMETHYL BENZENE | <p>Other Toxicity data is available for CHEMWATCH 12172 1,2,3-trimethylbenzene CHEMWATCH 2325 1,3,5-trimethylbenzene</p> <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p> <p>For trimethylbenzenes:</p> <p>Absorption of 1,2,4-trimethylbenzene occurs after oral, inhalation, or dermal exposure. Occupationally, inhalation and dermal exposures are the most important routes of absorption although systemic intoxication from dermal absorption is not likely to occur due to the dermal irritation caused by the chemical prompting quick removal. Following oral administration of the chemical to rats, 62.6% of the dose was recovered as urinary metabolites indicating substantial absorption. 1,2,4-Trimethylbenzene is lipophilic and may accumulate in fat and fatty tissues. In the blood stream, approximately 85% of the chemical is bound to red blood cells Metabolism occurs by side-chain oxidation to form alcohols and carboxylic acids which are then conjugated with glucuronic acid, glycine, or sulfates for urinary excretion. After a single oral dose to rats of 1200 mg/kg, urinary metabolites consisted of approximately 43.2% glycine, 6.6% glucuronic, and 12.9% sulfuric acid conjugates. The two principle metabolites excreted by rabbits after oral administration of 438 mg/kg/day for 5 days were 2,4-dimethylbenzoic acid and 3,4-dimethylhippuric acid. The major routes of excretion of 1,2,4-trimethyl- benzene are exhalation of parent compound and elimination of urinary metabolites. Half-times for urinary metabolites were reported as 9.5 hours for glycine, 22.9 hours for glucuronide, and 37.6 hours for sulfuric acid conjugates.</p> <p><b>Acute Toxicity</b> Direct contact with liquid 1,2,4-trimethylbenzene is irritating to the skin and breathing the vapor is irritating to the respiratory tract causing pneumonitis. Breathing high concentrations of the chemical vapor causes headache, fatigue, and drowsiness. In humans liquid 1,2,4-trimethylbenzene is irritating to the skin and inhalation of vapor causes chemical pneumonitis. High concentrations of vapor (5000-9000 ppm) cause headache, fatigue, and drowsiness. The concentration of 5000 ppm is roughly equivalent to a total of 221 mg/kg assuming a 30 minute exposure period (see end note 1). 2. Animals - Mice exposed to 8130-9140 ppm 1,2,4-trimethylbenzene (no duration given) had loss of righting response and loss of reflexes Direct dermal contact with the chemical (no species given) causes vasodilation, erythema, and irritation (U.S. EPA). Seven of 10 rats died after an oral dose of 2.5 mL of a mixture of trimethylbenzenes in olive oil (average dose approximately 4.4 g/kg). Rats and mice were exposed by inhalation to a coal tar distillate containing about 70% 1,3,5- and 1,2,4-trimethylbenzene; no pathological changes were noted in either species after exposure to 1800-2000 ppm for up to 48 continuous hours, or in rats after 14 exposures of 8 hours each at the same exposure levels. No effects were reported for rats exposed to a mixture of trimethyl- benzenes at 1700 ppm for 10 to 21 days</p> <p><b>Neurotoxicity</b> 1,2,4-Trimethylbenzene depresses the central nervous system. Exposure to solvent mixtures containing the chemical causes headache, fatigue, nervousness, and drowsiness. Occupationally, workers exposed to a solvent containing 50% 1,2,4-trimethylbenzene had nervousness, headaches, drowsiness, and vertigo (U.S. EPA). Headache, fatigue, and drowsiness were reported for workers exposed (no dose given) to paint thinner containing 80% 1,2,4- and 1,3,5-trimethylbenzenes</p> <p>Results of the developmental toxicity study indicate that the C9 fraction caused adverse neurological effects at the highest dose (1500 ppm) tested.</p> <p><b>Subchronic/Chronic Toxicity</b> Long-term exposure to solvents containing 1,2,4-trimethylbenzene may cause nervousness, tension, and bronchitis. Painters that worked for several years with a solvent containing 50% 1,2,4- and 30% 1,3,5-trimethylbenzene showed nervousness, tension and anxiety, asthmatic bronchitis, anemia, and alterations in blood clotting; haematological effects may have been due to trace amounts of benzene</p> <p>Rats given 1,2,4-trimethylbenzene orally at doses of 0.5 or 2.0 g/kg/day, 5 days/week for 4 weeks. All rats exposed to the high dose died and 1 rat in the low dose died (no times given); no other effects were reported. Rats exposed by inhalation to 1700 ppm of a trimethylbenzene isomeric mixture for 4 months had decreased weight gain, lymphopenia and neutrophilia.</p> |

|               |  |
|---------------|--|
|               | <p><b>Genotoxicity:</b> Results of mutagenicity testing, indicate that the C9 fraction does not induce gene mutations in prokaryotes (Salmonella typhimurium/mammalian microsome assay); or in mammalian cells in culture (in Chinese hamster ovary cells with and without activation). The C9 fraction does not induce chromosome mutations in Chinese hamster ovary cells with and without activation; does not induce chromosome aberrations in the bone marrow of Sprague-Dawley rats exposed by inhalation (6 hours/day for 5 days); and does not induce sister chromatid exchange in Chinese hamster ovary cells with and without activation.</p> <p><b>Developmental/Reproductive Toxicity:</b> A three-generation reproductive study on the C9 fraction was conducted CD rats (30/sex/group) were exposed by inhalation to the C9 fraction at concentrations of 0, 100, 500, or 1500 ppm (0, 100, 500, or 1500 mg/kg/day) for 6 hours/day, 5 days/week. There was evidence of parental and reproductive toxicity at all dose levels. Indicators of parental toxicity included reduced body weights, increased salivation, hunched posture, aggressive behavior, and death. Indicators of adverse reproductive system effects included reduced litter size and reduced pup body weight. The LOEL was 100 ppm; a no-observed-effect level was not established. Developmental toxicity, including possible developmental neurotoxicity, was evident in rats in a 3-generation reproductive study.</p> <p>No effects on fecundity or fertility occurred in rats treated dermally with up to 0.3 mL/rat/day of a mixture of trimethyl-benzenes, 4-6 hours/day, 5 days/week over one generation.</p> |
| <b>XYLENE</b> | <p>Reproductive effector in rats</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>The substance is classified by IARC as Group 3:<br/><b>NOT</b> classifiable as to its carcinogenicity to humans.<br/>Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>   |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✗ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✗ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✗ |
| <b>Mutagenicity</b>                      | ✗ | <b>Aspiration Hazard</b>        | ✓ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

| Duram S900              | Endpoint      | Test Duration (hr) | Species                       | Value         | Source        |
|-------------------------|---------------|--------------------|-------------------------------|---------------|---------------|
|                         | Not Available | Not Available      | Not Available                 | Not Available | Not Available |
| Stoddard Solvent        | Endpoint      | Test Duration (hr) | Species                       | Value         | Source        |
|                         | NOEC(ECx)     | 3072h              | Fish                          | 1mg/l         | 1             |
|                         | LC50          | 96h                | Fish                          | 2.2mg/l       | 4             |
|                         | NOEC(ECx)     | 720h               | Fish                          | 0.02mg/l      | 2             |
|                         | EC50          | 96h                | Algae or other aquatic plants | 0.277mg/l     | 2             |
|                         | LC50          | 96h                | Fish                          | 0.14mg/l      | 2             |
| 1,2,4-trimethyl benzene | Endpoint      | Test Duration (hr) | Species                       | Value         | Source        |
|                         | BCF           | 1344h              | Fish                          | 31-207        | 7             |
|                         | EC50(ECx)     | 96h                | Algae or other aquatic plants | 2.356mg/l     | 2             |
|                         | EC50          | 96h                | Algae or other aquatic plants | 2.356mg/l     | 2             |
|                         | EC50          | 48h                | Crustacea                     | ca.6.14mg/l   | 1             |
|                         | LC50          | 96h                | Fish                          | 3.41mg/l      | 2             |
| xylene                  | Endpoint      | Test Duration (hr) | Species                       | Value         | Source        |
|                         | LC50          | 96h                | Fish                          | 2.6mg/l       | 2             |
|                         | EC50          | 72h                | Algae or other aquatic plants | 4.6mg/l       | 2             |
|                         | EC50          | 48h                | Crustacea                     | 1.8mg/l       | 2             |
|                         | NOEC(ECx)     | 73h                | Algae or other aquatic plants | 0.44mg/l      | 2             |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

**DO NOT discharge into sewer or waterways.**

### Persistence and degradability

|                   |                                |                         |
|-------------------|--------------------------------|-------------------------|
| <b>Ingredient</b> | <b>Persistence: Water/Soil</b> | <b>Persistence: Air</b> |
|-------------------|--------------------------------|-------------------------|

| Ingredient              | Persistence: Water/Soil     | Persistence: Air            |
|-------------------------|-----------------------------|-----------------------------|
| 1,2,4-trimethyl benzene | LOW (Half-life = 56 days)   | LOW (Half-life = 0.67 days) |
| xylene                  | HIGH (Half-life = 360 days) | LOW (Half-life = 1.83 days) |

**Bioaccumulative potential**

| Ingredient              | Bioaccumulation    |
|-------------------------|--------------------|
| Stoddard Solvent        | LOW (BCF = 159)    |
| 1,2,4-trimethyl benzene | LOW (BCF = 275)    |
| xylene                  | MEDIUM (BCF = 740) |

**Mobility in soil**

| Ingredient              | Mobility          |
|-------------------------|-------------------|
| 1,2,4-trimethyl benzene | LOW (KOC = 717.6) |

**SECTION 13 Disposal considerations**

**Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|-------------------------------------|--|

**SECTION 14 Transport information**

**Labels Required**

|                         |   |
|-------------------------|---|
|                         |  |
| <b>Marine Pollutant</b> | NO  |
| <b>HAZCHEM</b>          | 3Y  |

**Land transport (ADG)**

|                                     |                       |                |
|-------------------------------------|-----------------------|----------------|
| <b>UN number or ID number</b>       | 1300                  |                |
| <b>UN proper shipping name</b>      | TURPENTINE SUBSTITUTE |                |
| <b>Transport hazard class(es)</b>   | Class                 | 3              |
|                                     | Subsidiary risk       | Not Applicable |
| <b>Packing group</b>                | III                   |                |
| <b>Environmental hazard</b>         | Not Applicable        |                |
| <b>Special precautions for user</b> | Special provisions    | 223            |
|                                     | Limited quantity      | 5 L            |

**Air transport (ICAO-IATA / DGR)**

|                                   |                       |                |
|-----------------------------------|-----------------------|----------------|
| <b>UN number</b>                  | 1300                  |                |
| <b>UN proper shipping name</b>    | Turpentine substitute |                |
| <b>Transport hazard class(es)</b> | ICAO/IATA Class       | 3              |
|                                   | ICAO / IATA Subrisk   | Not Applicable |

|                                     |   |       |
|-------------------------------------|---|-------|
|                                     | ERG Code  | 3L    |
| <b>Packing group</b>                | III   |       |
| <b>Environmental hazard</b>         | Not Applicable  |       |
| <b>Special precautions for user</b> | Special provisions  | A3    |
|                                     | Cargo Only Packing Instructions                           | 366   |
|                                     | Cargo Only Maximum Qty / Pack                             | 220 L |
|                                     | Passenger and Cargo Packing Instructions                  | 355   |
|                                     | Passenger and Cargo Maximum Qty / Pack                    | 60 L  |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions | Y344  |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack            | 10 L  |

**Sea transport (IMDG-Code / GGVSee)**

|                                     |                       |                |
|-------------------------------------|-----------------------|----------------|
| <b>UN number</b>                    | 1300                  |                |
| <b>UN proper shipping name</b>      | TURPENTINE SUBSTITUTE |                |
| <b>Transport hazard class(es)</b>   | IMDG Class            | 3              |
|                                     | IMDG Subrisk          | Not Applicable |
| <b>Packing group</b>                | III                   |                |
| <b>Environmental hazard</b>         | Not Applicable        |                |
| <b>Special precautions for user</b> | EMS Number            | F-E, S-E       |
|                                     | Special provisions    | 223            |
|                                     | Limited Quantities    | 5 L            |

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name            | Group         |
|-------------------------|---------------|
| Stoddard Solvent        | Not Available |
| 1,2,4-trimethyl benzene | Not Available |
| xylene                  | Not Available |

**Transport in bulk in accordance with the IGC Code**

| Product name            | Ship Type     |
|-------------------------|---------------|
| Stoddard Solvent        | Not Available |
| 1,2,4-trimethyl benzene | Not Available |
| xylene                  | Not Available |

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture****Stoddard Solvent is found on the following regulatory lists**

Australian Inventory of Industrial Chemicals (AIIC)  
Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

**1,2,4-trimethyl benzene is found on the following regulatory lists**

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

**xylene is found on the following regulatory lists**

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)  
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

**National Inventory Status**

| National Inventory                              | Status   |
|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes  |
| Canada - DSL                                    | Yes  |
| Canada - NDSL                                   | No (Stoddard Solvent; 1,2,4-trimethyl benzene; xylene) |
| China - IECSC                                   | Yes  |
| Europe - EINEC / ELINCS / NLP                   | Yes  |

Continued...

| National Inventory  | Status |
|---------------------|--------|
| Japan - ENCS        | Yes    |
| Korea - KECI        | Yes    |
| New Zealand - NZIoC | Yes    |
| Philippines - PICCS | Yes    |
| USA - TSCA          | Yes    |
| Taiwan - TCSI       | Yes    |
| Mexico - INSQ       | Yes    |
| Vietnam - NCI       | Yes    |
| Russia - FBEPH      | Yes    |

**Legend:** Yes = All CAS declared ingredients are on the inventory  
No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

## SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 10/03/2023 |
| Initial Date  | 14/12/2016 |

## SDS Version Summary

| Version | Date of Update | Sections Updated  |
|---------|----------------|---|
| 5.1     | 23/12/2022     | Classification review due to GHS Revision change.                     |
| 6.1     | 10/03/2023     | Classification change due to full database hazard calculation/update. |

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average  
 PC – STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 ES: Exposure Standard  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index  
 AIIC: Australian Inventory of Industrial Chemicals  
 DSL: Domestic Substances List  
 NDSL: Non-Domestic Substances List  
 IECSC: Inventory of Existing Chemical Substance in China  
 EINECS: European INventory of Existing Commercial chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 NLP: No-Longer Polymers  
 ENCS: Existing and New Chemical Substances Inventory  
 KECI: Korea Existing Chemicals Inventory  
 NZIoC: New Zealand Inventory of Chemicals  
 PICCS: Philippine Inventory of Chemicals and Chemical Substances  
 TSCA: Toxic Substances Control Act  
 TCSI: Taiwan Chemical Substance Inventory  
 INSQ: Inventario Nacional de Sustancias Químicas  
 NCI: National Chemical Inventory  
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.