



Durascrim A70 & Duramscrim PF

Polyester Reinforcing Fabric for use with Duram Waterproofing Membranes and Coatings

PRODUCT DESCRIPTION

Durascrim A70 & Duramscrim PF is an open weave polyester reinforcing fabric for the use of reinforcing Duram waterproofing membranes.

USAGE/PURPOSE

- ❑ As a reinforcing fabric, Duram Durascrim A70 or Duramscrim PF is suitable to use with the following Duram Membranes: Durabit EF, Durabit RE0, Durabit-Bitumen Free, Azcoflex, Pondseal, Duram 195 and Multithane Range. Refer to product data sheet for the particular Duram waterproofing product.
- ❑ Reinforcing membranes with Durascrim A70 or Duramscrim PF is recommended over joins, cracks, gaps and in corners or wherever additional tensile strength or membrane build up is desired.

FEATURES & BENEFITS

- ❑ Provides additional strength to waterproofing membranes.
- ❑ Allows greater product build up.

PACKAGING

- ❑ Durascrim A70: 140mm x 100m
- ❑ Durascrim PF: 150mm x 91.5m

COLOUR

Durascrim A70 & Duramscrim PF comes in white.

STORAGE

Store in cool, dry area.

COVERAGE/YIELD

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.


Generally, at least 2 Lt per m² of product is needed to properly saturate and cover Durascrim A70 & Duramscrim PF.

APPLICATION

- ❑ Apply 1st coat of the Duram membrane, usually at no less than 500 microns thick, and embed the Durascrim A70 or Duramscrim PF into wet coat. Apply a similar saturating coat over and working it in to the Durascrim A70 or Duramscrim PF ensuring that there are no wrinkles, folds or bubbles in fabric and sufficient product has been applied to cover the fabric.
- ❑ Allow to dry. Apply 1 to 2 additional coats at 500 microns thick and allow to dry.
- ❑ Refer to product data sheets of the Duram membrane in question.

SPECIFICATION

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement. The applicator or contractor must use their skill, knowledge, and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the company in writing.



HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

CONDITIONS OF USE AND DISCLAIMER

The information contained in this TDS is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the TDS in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

TREMCO CPG AUSTRALIA

Duram a division of Tremco CPG Australia
ABN: 25 000 024 064
12/4 Southridge Street
Eastern Creek, NSW 2766

P: (02) 9624 4077
F: (02) 9624 4079
E: duram@duram.com.au