



# Durascrim

Polyester Reinforcing Fabric For Use With Duram Membranes and Coatings

## PRODUCT DESCRIPTION

Open weave polyester reinforcing fabric for the use of reinforcing Duram waterproofing membranes.

## USAGE/PURPOSE

- ❑ As a reinforcing fabric, Duram Durascrim is suitable to use with the following Duram Membranes: Durabit EF, Durabit REO, Azcothane Range, Azcoflex, Pondseal, Duram 195 and Multithane Range.
- ❑ Reinforcing membranes with Durascrim is recommended over joints, cracks, gaps and in corners or wherever additional tensile strength or membrane build up is desired.

## FEATURES & BENEFITS

- ❑ Provides additional strength to waterproofing membranes.
- ❑ Allows greater product build up.

## PACKAGING

- ❑ 100mm x 50m
- ❑ 150mm x 50m
- ❑ 1200mm x 50m
- ❑ 140mm x 100m (Durascrim A70)
- ❑ 150mm x 91.5m (PermaFab - known as Durascrim PF)

## COLOUR

White.

## SHELF LIFE

12 months.

## STORAGE

Store in dry area.

## COVERAGE/YIELD

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Generally, at least 2Lt per m<sup>2</sup> of product is needed to properly saturate and cover Durascrim.

## SURFACE PREPARATION

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

## APPLICATION

- ❑ Apply 1st coat of the Duram membrane, usually at no less than 500 microns thick, and embed the Durascrim into wet coat.
- ❑ Apply a similar saturating coat over and working it in to the Durascrim ensuring that there are no wrinkles, folds or bubbles in fabric and sufficient product has been applied to cover the fabric.
- ❑ Allow to dry.
- ❑ Apply 1 to 2 additional coats at 500 microns thick and allow to dry.

Refer to product data sheets of the Duram membrane in question.



## SPECIFICATION

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement. The applicator or contractor must use their skill, knowledge, and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the company in writing.

## HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

## CONDITIONS OF USE AND DISCLAIMER

The information contained in this TDS is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the TDS in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

## TREMCO CPG AUSTRALIA

Duram a division of Tremco CPG Australia

ABN: 25 000 024 064

12/4 Southridge Street

Eastern Creek, NSW 2766

P: (02) 9624 4077

F: (02) 9624 4079

E: duram@duram.com.au