



Maxi-Trowel

Trowel-on Decorative Scratch Coat

Description

MAXITROWEL is a premium, pigmented (or neutral), high performance, high build acrylic scratch coat incorporating special graded aggregates. MAXITROWEL is formulated for ease of application and patterning. The thickness and texture is controlled by the graded aggregates and is available in 1.5mm, 2 mm and 3 mm. Minimum quantities may apply. MAXITROWEL is applied by trowel and finished to the required pattern, usually vertical lines or random swirl over suitably primed surfaces. MAXITROWEL needs to be overcoated with SUPREME or MAXIFLEX (top coat) to give extra protection from weather conditions and to achieve a vibrant finish.

Uses

MAXITROWEL may be applied on primed internal and external walls. Due to its high build most substrate imperfections can be hidden or obscured.

Suitable Surfaces

Suitable for application on sound, primed off - form concrete, cement render, FC sheeting, Harditex sheeting (or similar), other concrete products and brick surfaces. Substrates and or joints may need to be prepared or skimmed with MAXIJOINT, MAXICRETE or MAXIPATCH .

Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

Limitations

Do not apply if rain or frost is imminent or possible before the product has properly dried. The product should not be subjected to hydrostatic pressure and excessive rising damp. Ambient temperature: Min. 10°C Max. 35°C Surface temperature: Min. 5°C Max. 50°C

Benefits and Advantages

- Ease of application & patterning.
- Excellent adhesion.
- Excellent weathering & abrasion resistance.
- Resistance to saponification under alkali conditions.
- Allows surface to breathe.
- Application safety, water based, non combustible.
- High tensile strength.
- Top coating is optional but highly recommended.

Precautions in Use

The product is safe to use if used properly. The use of gloves, goggles and coveralls is recommended while applying MAXITROWEL.

Priming and Surface Preparation

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

Prime surface with MAXIPRIME. Allow to dry for approximately 4 hours before application of MAXITROWEL.

Cracks must be filled with suitable filler and finished flush accordance with good painting practice. A penetrating sealer may be required.

Application

Apply MAXITROWEL evenly over primed surface with a steel trowel as determined by the gauging stones. When product starts to set, pattern surface by rolling the gauging aggregate using a polystyrene float. When product has cured apply the top coat of either SUPREME or MAXIFLEX as recommended by the manufacturer but this is optional.

Application Experience

We recommend that the product is applied by person with the appropriate skills and experience for the type of product. The acceptability of the surface is the responsibility of the applicator.

Coverage

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

The following approximate average spread rate per 15 litre pail applied is: 1.5 mm: 10 to 12 sq.m. 2.0 mm: 8 sq.m. 3.0 mm: 6 sq.m. This is a guide only and will depend on the information above.

Colours

Available in a wide range of colours, deep or dark colours make attract a tinting fee.

Colour Batches

Whilst care is taken to accurately colour match, batch to batch variations may occur for reasons which may be beyond our control. We strongly advise that project requirements are ordered in a single batch lot to avoid colour matching from batch to batch. Minimum quantities and tinting charges may apply.

Contractor Responsibility

It is the responsibility of the contractor or applicator to ensure that the colour is within specification prior to its application. The Company shall not be liable for any colour variations after the product has been applied. Further, the applicator should use product for touch-ups from the same batches used to do the original coats.

Drying and Curing

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

Touch Dry: 2 to 4 hours at 20°C. Hard Dry: 2 to 4 days.

Storage

Available in 4 and 15 Lt Pails. Shelf life: 6 to 12 months in unopened containers. Store in cool dry area. Containers should be rotated to prevent settlement.

Clean Up

Wet spills can be cleaned with water. Ensure product does not enter drains.

Safety & Precautions

The use of gloves, goggles and coveralls is recommended as the product may irritate skin and eyes. If swallowed give water to drink and seek medical assistance. If in eyes, flush thoroughly with clean water, holding lid open to ensure any trapped product is flushed away. If on skin, remove contaminated clothing and wash with soap and water. Do not use solvents. If inhaled, unlikely due to viscosity of product, remove person to fresh air and apply artificial respiration if required.

For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

Issued: 1 May 2012 | Valid to: 31 May 2021

Conditions of Use and Disclaimer

The information contained in this Material Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

DURAM PTY LTD ABN 50 612 836 718

The Ultimate in Waterproofing & Protective Coating Technology

Duram Offices:

NEW SOUTH WALES: 51 Prince William Drive, Seven Hills, NSW 2147

Tel (02) 9624 4077 Fax: (02) 9624 4079

QUEENSLAND: Unit 4, 29 Collinsvale St Rocklea, QLD 4106

Tel (07) 3255 6478 Fax: (07) 3255 6258