



Maximesh

Jointing tape - Mesh for reinforcing joints in conjunction with MaxiJoint

Description

Maximesh is an open weave reinforcing jointing tape specifically used with Maxijoint and Maxicrete to fill joints in blue board and FC sheeting. The system provides a solid and flexible joint as preparation for architectural top coats and finishes. Available in rolls of 50mm x 50m , 150mm x 50m and 1.2m x 50m.

Uses

Part of jointing system for blue board and FC sheeting.

Suitable Surfaces

Blue Board and FC sheeting. Refer MaxiJoint data sheet.

Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

Benefits and Advantages

Easy to use

Strong

Compatible with Maxijoint and Maxicrete together forming an excellent jointing system.

Priming and Surface Preparation

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

N/A

Application

Refer Maxijoint data sheet.

Application Experience

We recommend that the product is applied by person with the appropriate skills and experience for the type of product. The acceptability of the surface is the responsibility of the applicator.

Colours

Natural.

Colour Batches

Whilst care is taken to accurately colour match, batch to batch variations may occur for reasons which may be beyond our control. We strongly advise that project requirements are ordered in a single batch lot to avoid colour matching from batch to batch. Minimum quantities and tinting charges may apply.

Contractor Responsibility

It is the responsibility of the contractor or applicator to ensure that the colour is within specification prior to its application. The Company shall not be liable for any colour variations after the product has been applied. Further, the applicator should use product for touch-ups from the same batches used to do the original coats.

Safety & Precautions

Requires cutting. All normal precautions regarding use of sharp instruments should be observed. For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

Issued: 1 May 2012 | Valid to: 31 May 2021

Conditions of Use and Disclaimer

The information contained in this Material Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

DURAM PTY LTD ABN 50 612 836 718

The Ultimate in Waterproofing & Protective Coating Technology

Duram Offices:

NEW SOUTH WALES: 51 Prince William Drive, Seven Hills, NSW 2147

Tel (02) 9624 4077 Fax: (02) 9624 4079

QUEENSLAND: Unit 4, 29 Collinsvale St Rocklea, QLD 4106

Tel (07) 3255 6478 Fax: (07) 3255 6258