



# Prestige Sandstone

Trowel-on Texture Coating Giving a 'Sandstone' Finish.

---

## Description

PRESTIGE is a premium, pigmented ( or neutral ), high performance, flexible high build acrylic incorporating special graded aggregates, fillers and sand. PRESTIGE is a trowel applied decorative coating providing a stylish coloured 'sandstone' appearance. PRESTIGE is generally tinted and does not require to be top coated, but surfaces must be primed prior to the application of the product. PRESTIGE is available in fine, standard and coarse grades.

---

## Uses

PRESTIGE may be used on suitably primed internal and external walls providing a decorative, protective coating/finish. Due to its high build most substrate imperfections can be hidden or obscured.

---

## Suitable Surfaces

PRESTIGE is suitable to be applied to primed, sound off form concrete, cement render, fibre - cement sheeting, Harditex sheeting, other concrete products and brick surfaces. Substrate or joints may need to be prepared with MAXIJOINT and/or MAXICRETE. NB: See appropriate Product Data Sheets.

---

## Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

## Limitations

Ambient temperature: Min. 10°C Max. 35°C. Surface temperature: Min. 5°C Max. 50°C Do not apply if rain or frost is imminent or possible before product has properly dried. The product should not be subjected to hydrostatic pressure and excessive rising damp. Not suitable for foot traffic.

## Benefits and Advantages

- Ease of application.
- Excellent adhesion to primed surface.
- Excellent weathering & abrasion resistance.
- Allows surface to breath.
- Application safety, water based, non combustible.
- High tensile strength.

## Precautions in Use

The use of gloves and goggles is recommended as the product may irritate skin and eyes.

## Priming and Surface Preparation

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion. Prime surface with MAXIPRIME which can be tinted as close as possible to the PRESTIGE colour if required a premium may be charged. Allow to dry for approximately 4 hours before top coating.

## Application

Apply PRESTIGE evenly with a trowel. It is recommended that the product be thoroughly stirred using a power stirrer prior to application. Do not apply if rain or frost is imminent or possible before the product has properly dried. The product should not be subjected to hydrostatic pressure and excessive rising damp. Ensure surface has been primed using MAXIPRIME prior to the application of the PRESTIGE. MAXIPRIME should be left to dry for at least 4 hours in good drying conditions.

### Application Experience

We recommend that the product is applied by person with the appropriate skills and experience for the type of product. The acceptability of the surface is the responsibility of the applicator.

### Coverage

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Average approximate spread rate is 18 to 20 sq. m per 15 litre pail. But this may vary dependent upon type, condition and porosity of the substrate and application technique. MAXIPRIME: Undiluted - 6 to 8 sq. m per litre . Diluted - +/- 14 sq. m per litre with the addition of 30% clean water.

### Colours

Available in a wide range of colours, made to order.

#### Colour Batches

Whilst care is taken to accurately colour match, batch to batch variations may occur for reasons which may be beyond our control. We strongly advise that project requirements are ordered in a single batch lot to avoid colour matching from batch to batch. Minimum quantities and tinting charges may apply.

#### Contractor Responsibility

It is the responsibility of the contractor or applicator to ensure that the colour is within specification prior to its application. The Company shall not be liable for any colour variations after the product has been applied. Further, the applicator should use product for touch-ups from the same batches used to do the original coats.

### Drying and Curing

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

Touch Dry: 2 to 4 hours at 20°C Hard Dry: 2 to 4 days

### Storage

Store in dry, cool area and protect from heat, frost, moisture and damage. Available in 15 Lt Pails. Shelf Life: 6 months in unopened containers. Containers should be rotated to prevent settlement.

### Clean Up

Wet spills can be cleaned with water. Ensure product does not enter the drains. Care must be taken to avoid damaging the coating.

### Safety & Precautions

The use of gloves and goggles is recommended as the product may irritate skin and eyes. If product is in eyes, flush with thoroughly with clean water. If on skin, remove contaminated clothing and wash with soap and water. Do not use solvent. If inhaled, unlikely due to the viscosity of the product, remove person to fresh air and apply artificial respiration if required. For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

Issued: 1 May 2012 | Valid to: 31 May 2021

### Conditions of Use and Disclaimer

The information contained in this Material Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

**DURAM PTY LTD** ABN 50 612 836 718

**The Ultimate in Waterproofing & Protective Coating Technology**

#### Duram Offices:

**NEW SOUTH WALES:** 51 Prince William Drive, Seven Hills, NSW 2147

Tel (02) 9624 4077 Fax: (02) 9624 4079

**QUEENSLAND:** Unit 4, 29 Collinsvale St Rocklea, QLD 4106

Tel (07) 3255 6478 Fax: (07) 3255 6258