



SUPREME

HIGH BUILD, DECORATIVE, ACRYLIC, ROLL-ON, TEXTURE COATING

DESCRIPTION

SUPREME is a high performance, high solids, high build acrylic based decorative texture paint coating in a satin finish. It provides a weather durable, seamless, water-resistant, flexible roll-on coating which can be tinted to create almost unlimited colours. Depending upon application technique a range of finishes can be achieved from smooth (flat) to stippled. Supreme can manufactured to a semi-gloss or flat finish.

The Duram Brand has been an industry leader for over 30 years.

USES

SUPREME is ideal as an internal or external final decorative and protective coating.

SUITABLE SURFACES

SUPREME is suitable to coat the following suitably primed, clean, dry, sound, contaminant-free, stable surface.

- Walls
- Facades
- Balustrades
- Columns
- Partitioning
- Top Coat over: **MAXITROWEL, MAXITEX, MAXIPATCH, MAXIRENDERS, MAXIJOINT, MAXICRETE.**
- Surface imperfections should be fixed prior to the application of the **SUPREME** to achieve the desired result. Substrates/ joints may need to be prepared with **MAXIJOINT, MAXICRETE** or **MAXIPATCH**. NB: Refer Product Data Sheets.
- Off-form Concrete
- Concrete
- Cement Render
- Block & Brick work
- CSR Hebel
- FC and Blue Board Sheeting
- Plaster Board

BENEFITS AND ADVANTAGES

- High performance coating designed for long lasting protection and aesthetics.
- Easy to apply and maintain.
- Excellent weathering properties.
- Excellent adhesion.
- Flexible.
- Dirt pick-up resistance.
- Washable.
- Allows surface to breathe.
- Environmentally friendly.
- Looks great on many surfaces.
- Versatile.

SPECIFICATION

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement, but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

LIMITATIONS

- The product should not be applied outside the ambient temperature of 10°C to 35°C or surface temperature of 10°C to 45°C.
- If exposed to the weather, do not apply if rain or inclement weather is imminent or possible before the product can properly dry.
- Not suitable for foot traffic.

PRECAUTIONS IN USE

The product is safe to use if used properly.

SURFACE PREPARATION

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

Surface imperfection should be repaired prior to coating to achieve a good result and desired finish. Surfaces may require patching, skimming or rendering using **MaxiCrete** (smooth patching & skimming compound), **Maxipatch** (polymer render), **MaxiJoint** (flexible jointing compound).

Cracks should be filled with a suitable filler and finished flush with the surface in accordance with good painting practice.

PRIMING

Prime surfaces with **Maxiprime**. Refer to **Maxiprime's** product data sheet.

In general: Apply at the rate of 6m² to 8m² per litre per coat (average of 90m² per 15 litre pail), usually applied in one coat. If tinted, do not dilute as dilution will affect and change the colour. Allow to dry for about 4 hours in good drying conditions before applying **SUPREME**.

Excessively porous surface may require an additional priming coat.

APPLICATION

Stir product well before use. (Power Stirrer)

Apply by roller (conventional or black texture) or by air-less spray in a minimum of two coats.

Ambient temperature: Min. 10°C Max. 35°C

Surface temperature: Min. 5°C Max. 50°C

Do not apply **SUPREME** if rain or frost is imminent or possible before the product has properly dried.

Application Experience: We recommend that the product is applied by person with the appropriate skills and experience for the type of product. The acceptability of the surface is the responsibility of the applicator.

COVERAGE

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Coverage may vary as it is dependent upon the type, texture, porosity and application technique. 70 to 75m² per 15 litre pail (about 5m² per litre) per coat applied with a low to medium nap roller. Supreme requires two coats. 45m² per 15 litre pail (about 3m² per litre) per coat applied with a medium black texture roller.

COLOURS

SUPREME can be tinted to almost any colour. A batch to batch tint-matching charge may be levied. Arrangements can be made for the piecemeal supply of product. Colours and particular batch to batch colour-matching should be checked prior to application. No responsibility will be accepted after the product has been used and/or applied. Colours produced from white and light bases are usually included in the price of the product. A premium may be charged for colours produced from deep and accent bases.

Colour Batches: Whilst care is taken to accurately colour match, batch to batch variations may occur for reasons which may be beyond our control. We strongly advise that project requirements are ordered in a single batch lot to avoid colour matching from batch to batch. Minimum quantities and tinting charges may apply.

Contractor Responsibility: It is the responsibility of the contractor or applicator to ensure that the colour is within specification prior to its application. The Company shall not be liable for any colour variations after the product has been applied. Further, the applicator should use product for touch-ups from the same batches used to do the original coats.

DRYING AND CURING

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

At 20°C and 50% RH, cure times would be approximate: Touch dry: 2 to 4 hours Recoat: 6 hours

STORAGE

Available in 4 and 15 litre pails.

Shelf life about 6 months in unopened containers. Store in cool, dry area. Product is not flammable or considered dangerous. Containers should be rotated to prevent settlement.

CLEAN UP

Wet spills can be cleaned with water.

TILING, TOPPING OR TOP COATING

Not applicable.

SAFETY & PRECAUTIONS

The use of gloves and goggles is recommended. If swallowed give water to drink and seek medical advice. If in eyes, flush thoroughly with clean water, holding open the lid to ensure that any trapped product is flushed away. If on skin, remove contaminated clothing and wash with soap and water. If inhaled, unlikely due to viscosity of the product, remove to fresh air and apply artificial respiration if required. Seek urgent medical attention.

For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

CONDITIONS OF USE AND DISCLAIMER

The information contained in this TDS is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the TDS in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Version: 001-052021

DURAM ABN 25 000 024 064

A DIVISION OF TREMCO CPG AUSTRALIA PTY LTD

The Ultimate in Waterproofing & Protective Coating Technology

Duram Offices:

NEW SOUTH WALES: 51 Prince William Drive, Seven Hills, NSW 2147

Tel (02) 9624 4077 Fax: (02) 9624 4079

QUEENSLAND: 63 Radley Street, Virginia, QLD 4014

Tel (07) 3255 6478 Fax: (07) 3255 6258