



# Supreme

High Build, Decorative, Acrylic, Roll-on, Texture Coating

---

## Description

SUPREME is a high performance, high solids, high build acrylic based decorative texture paint coating in a satin finish. It provides a weather durable, seamless, water-resistant, flexible roll-on coating which can be tinted to create almost unlimited colours. Depending upon application technique a range of finishes can be achieved from smooth (flat) to stippled. Supreme can be manufactured to a semi-gloss or flat finish.

---

## Uses

SUPREME is ideal as an internal or external final decorative and protective coating for: Walls. Facades. Balustrades. Columns. Partitioning. and top coat over: MAXITROWEL. MAXITEX. MAXIPATCH. MAXIRENDERS. MAXIJOINT. MAXICRETE.

---

## Suitable Surfaces

SUPREME is suitable to coat the following suitably primed, clean, dry, sound, contaminant-free, stable surface:

- Off-form concrete, concrete / cement block work and brick work
- CSR Hebel
- Cement render
- FC Sheeting, Blue Board and plaster board.

Surface imperfections should be fixed prior to the application of the SUPREME to achieve the desired result. Substrates/joints may need to be prepared with MAXIJOINT, MAXICRETE or MAXIPATCH.

---

## Specification

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

## Limitations

The product should not be applied outside the ambient temperature of 10oC to 35oC or surface temperature of 10oC to 45oC. If exposed to the weather, do not apply if rain or inclement weather is imminent or possible before the product can properly dry. Not designed for foot traffic.

## Benefits and Advantages

High performance coating designed for long lasting protection and aesthetics.  
Easy to apply and maintain.  
Excellent weathering properties.  
Excellent adhesion.  
Flexible.  
Dirt pick-up resistance.  
Washable.  
Allows surface to breathe.  
Environmentally friendly.  
Looks great on many surfaces.  
Versatile.

## Precautions in Use

The product is safe to use if used properly.

## Priming and Surface Preparation

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of dust, loose, flaking, friable material and substances that may diminish adhesion.

Surface imperfection should be repaired prior to coating to achieve a good result and desired finish. Surfaces may require patching, skimming or rendering using MaxiCrete [smooth patching & skimming compound], Maxipatch [polymer render], MaxiJoint (flexible jointing compound)].

Cracks should be filled with a suitable filler and finished flush with the surface in accordance with good painting practice.

**Priming:**

Prime surfaces with Maxiprime. Refer to Maxiprime's product data sheet.

In general: Apply at the rate of 6m<sup>2</sup> to 8m<sup>2</sup> per litre per coat (average of 90 sq.m. per 15 litre pail), usually applied in one coat. If tinted, do not dilute as dilution will effect and change the colour. Allow to dry for about 4 hours in good drying conditions before applying SUPREME.

Excessively porous surface may require an additional priming coat.

## Application

Stir product well before use.(Power Stirrer)

Apply by roller (conventional or black texture) or by air-less spray in a minimum of two coats.

Ambient temperature: Min. 10°C Max. 35°C

Surface temperature: Min. 5°C Max. 50°C

Do not apply SUPREME if rain or frost is imminent or possible before the product has properly dried.

**Application Experience**

We recommend that the product is applied by person with the appropriate skills and experience for the type of product. The acceptability of the surface is the responsibility of the applicator.

## Coverage

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Coverage may vary as it is dependent upon the type, texture, porosity and application technique. 70 to 75 sq.m. per 15 litre pail (about 5 sq.m. per litre) per coat applied with a low to medium nap roller. Supreme requires two coats. 45 sq.m. per 15 litre pail (about 3 sq.m. per litre) per coat applied with a medium black texture roller.

## Colours

SUPREME can be tinted to almost any colour. A batch to batch tint-matching charge may be levied. Arrangements can be made for the piecemeal supply of product. Colours and particular batch to batch colour-matching should be checked prior to application. No responsibility will be accepted after the product has been used and/or applied. Colours produced from white and light bases are usually included in the price of the product. A premium may be charged for colours produced from deep and accent bases.

**Colour Batches**

Whilst care is taken to accurately colour match, batch to batch variations may occur for reasons which may be beyond our control. We strongly advise that project requirements are ordered in a single batch lot to avoid colour matching from batch to batch. Minimum quantities and tinting charges may apply.

**Contractor Responsibility**

It is the responsibility of the contractor or applicator to ensure that the colour is within specification prior to its application. The Company shall not be liable for any colour variations after the product has been applied. Further, the applicator should use product for touch-ups from the same batches used to do the original coats.

## Drying and Curing

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

At 20°C and 50% RH, cure times would be approximate: Touch dry: 2 to 4 hours Recoat: 6 hours

## Storage

Available in 4 and 15 litre pails. Shelf life about 6 months in unopened containers. Store in cool, dry area. Product is not flammable or considered dangerous. Containers should be rotated to prevent settlement.

## Clean Up

Wet spills can be cleaned with water.

## Tiling, Topping or Top Coating

Not Applicable.

## Safety & Precautions

The use of gloves and goggles is recommended. If swallowed give water to drink and seek medical advice. If in eyes, flush thoroughly with clean water, holding open the lid to ensure that any trapped product is flushed away. If on skin, remove contaminated clothing and wash with soap and water. If inhaled, unlikely due to viscosity of the product, remove to fresh air and apply artificial respiration if required. Seek urgent medical attention.

For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

## Conditions of Use and Disclaimer

The information contained in this Material Data Sheet is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the Product Data Sheet in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

**DURAM PTY LTD** ABN 50 612 836 718

**The Ultimate in Waterproofing & Protective Coating Technology**

**Duram Offices:**

**NEW SOUTH WALES:** 51 Prince William Drive, Seven Hills, NSW 2147

Tel (02) 9624 4077 Fax: (02) 9624 4079

**QUEENSLAND:** Unit 4, 29 Collinsvale St Rocklea, QLD 4106

Tel (07) 3255 6478 Fax: (07) 3255 6258